

ZURRPUNKTE FÜR LADUNGSSICHERUNG

TWN 1473, TWN 1471, TWN 1880

- 100% rissgeprüft
- Erfüllt Anforderungen der EN 12640 und EN 12195-3
- Kennzeichnung der Zurrkraft in daN

TWN 1473

- In 8.000 daN und 13.500 daN verfügbar
- 180° schwenkbar
- Kompakte Bauweise



TWN 1471


- In 5.000 daN und 10.000 daN verfügbar
- Schwenkbereich von 30° bis 150°
- lange Lebensdauer
- Versenkbar (Unfallvermeidung)
- Einfache und sichere Montage an Seitenrahmen



TWN 1880

- Von 3.000 daN bis 20.000 daN verfügbar
- 180° schwenkbar
- Geringe Einbauhöhe aufgrund kompakter Bauweise
- Feste Positionierung und geräuscharm durch Feder





LASHING POINTS FOR SECURING OF LOADS

TWN 1473, TWN 1471, TWN 1880

- 100% crack tested
- Complies with EN 12640 and EN 12195-3
- Marked with Lashing Capacity (LC) in daN

TWN 1473

- Available in 8.000 daN and 13.500 daN
- 180° pivotable
- Compact design



TWN 1471

- Available in 5.000 daN and 10.000 daN
- Swivel range from 30° – 150°
- Long service life
- Retractable (accident prevention)
- Easy and safe mounting at the side frames



TWN 1880

- Available in 3.000 daN up to 20.000 daN
- 180° pivotable
- Low mounting height due to compact design
- Fixed positioning and noise damped by springs

